

AV8365 8 Megapixel 360 Degree Panoramic Camera

Bid-Spec

1.0 Description

The AV8365 series camera is dual encoder (H.264 & MJPEG), 8 Megapixel resolution, IP addressable 360 degree panoramic camera. It is designed to deliver full motion high definition progressive scan digital video across local area networks. The AV8365 has a high sensitivity, and is PoE (IEEE 802.3af) compliant. Built with Arecont Vision's proprietary massively-parallel multi-sensor SurroundVideo® technology, the AV8365 has the ability to output multiple image formats allowing the simultaneous viewing of the full resolution field of view and regions of interest for high definition forensic zooming. This camera offers over six times the resolution per sensor or 24 times the field of view across the entire panorama compared to standard resolution IP cameras.

2.0 Bid Specification

- The camera shall utilize four high sensitivity 2 Megapixel CMOS sensors each with 1/2" optical format
- The camera shall be H.264 (MPEG4, Part 10) compliant
- The camera shall have dual standard compression support with simultaneous streaming of both H.264 and MJPEG formats
- The camera shall have multi-streaming support of up to 8 non-identical concurrent streams (different frame rate, bit rate, resolution, quality, and compression format).
- The camera shall have bit rate control for full view, multi view, and archiving
- The camera's bit rate control shall be selectable from 100 Kbps to 10 Mbps for each independent stream.
- The camera shall have Real Time Streaming Protocol (RTSP) support allowing for compatibility with media players such as Windows Media Player, Apple QuickTime, VLC Player and others.
- The cameras H.264 implementation shall maintain full real time video frame rates.
- The camera shall output at a maximum resolution of 1600(H) x 1200(V) pixels per sensor for a total resolution of 6400(H) x 1200(V) across all for sensors
- The cameras maximum frame rate shall be 22 frames per second across all four sensors at the maximum resolution
- The cameras maximum frame rate shall be 88 frames per second across all four sensors at the maximum resolution of 800(H) x 600(V) per sensor
- The camera shall use four 8mm lenses that shall be pre-mounted on the camera
- The cameras overall imaging shall provide a 360 degree field of view
- The camera shall feature streaming of the full field of view (FOV) and multiple regions of interest (ROI) for forensic zooming
- The camera shall be equipped with a 100 Mbps LAN connector and can deliver image data at a maximum data rate of up to 55 Megabits per second (55 Mbps)
- The camera shall provide 21 levels of compression quality for optimal viewing and archiving
- The camera shall support a minimum TFTP, HTTP, and RTSP/RTP network protocols
- Each sensor of the camera shall feature automatic exposure, automatic multi-matrix white balance, shutter speed control, programmable brightness, saturation, gamma and sharpness
- The camera shall also feature selectable 50/60 Hz flicker control, windowing and decimation, simultaneous delivery of full-field view and zoomed images at video frame rate, instantaneous electronic zoom, pan and tilt, and electronic image rotation by 180 degrees
- The camera shall incorporate necessary algorithms and circuits to detect motion in low light with clarity
- The camera shall support a minimum illumination of 0.2 Lux @ F2.0 in color mode

- The camera's primary power source shall be Power over Ethernet (PoE) complying with the IEEE 802.3af standard
- The camera shall have the alternative option to be powered from a 12V DC up to 48V DC or 24V AC power source providing at least 8.0W of power
- This camera shall feature a durable aluminum housing that minimizes fire hazards.
- The camera should be mounted using a customized interior dome, exterior dome or recessed mounting kit.
- The camera's operating ambient temperature is 0°C (32°F) to 50°C (122°F).
- The camera shall be FCC Part 15, Class A and CE compliant
- The camera shall have dimensions of: 6.49"H (164.8 mm) x 6.0" dia. (152.4 mm) weighing 4lbs (1815g)

Quick-Spec

3.0 Minimum Performance Specification

Megapixel camera must meet the following operating requirements

Operational

Imaging	Four 2 megapixel CMOS image sensors 1/2" optical format Bayer mosaic RGB filter
Active Pixel Count	1600(H) x 1200(V) pixel array per sensor 6400(H) x 1200(V) pixels across all four sensors
Minimum illumination	Color: 0.2 Lux @ F2.0
Dynamic range	60 dB
Maximum SNR	45 dB

Full Field of View (FOV) Resolutions per Sensor

1600(H) x 1200(V)	2 megapixel
800(H) x 600(V)	1/4 resolution

Cropped Field of View Resolutions per Sensor

1280x1024 1.3 MP
1280x720 HDTV - 720p
1024x768 XGA
800x600 SVGA
704x570 PAL
704x480 NTSC
640x480 VGA
352x288 CIF
320x240 SIF

Data Transmission

Data rate

bit rate control from 100Kbps to 10Mbps
bit rate control available for full view, multi view, and archive
unthrottled bandwidth up to 55Mbps

Video frame rate up to:

88fps @ 800x600
22fps @ 1600x1200

Compression type

H.264 (MPEG4, Part 10)
Motion JPEG
21 levels of quality

Transmission protocols

TFTP, HTTP, RTSP
100 Base-T Ethernet Network Interface

Programmability

Auto Exposure (AE) and Gain Control (AGC) >120dB
On-camera real-time motion detection with 64 detection zones
Programmable backlight compensation
Auto multi-matrix white balance
50/60Hz selectable flicker control
Electronic pan, tilt, zoom (PTZ)
Electronic image flip - 180 degree rotation
Resolution windowing down to 32x32 pixels window
Programmable shutter speed to minimize motion blur
MoonLight™ mode - extended exposure and proprietary noise cancellation
Programmable resolution, brightness, saturation, gamma, sharpness, tint
Picture-in-Picture: simultaneous delivery of full field of view and zoomed images
Bandwidth & storage savings by running at 1/4 resolution

Electrical

Power over Ethernet (PoE): PoE 802.3af
DC input: auxiliary 12V-48V DC
AC input: auxiliary 24V AC
Power consumption 8.0 Watts maximum

Mechanical

Dimensions(H x W x D) 6.49"H (164.8 mm) x 6.0" dia. (152.4 mm)
Weight 4 lbs (1815g)
Lens C lens mount – Four 8mm lenses included

Environmental

Operating temperature 0°C (32 °F) to +50°C (122 °F)
Storage temperature -20°C (-4 °F) to +60°C (140 °F)
Humidity 0% to 90% (non condensing)

Regulatory

FCC and CE compliant

Related Documentation

1. AV User Manual
2. AV Software Developer Kit Manual
3. AV8185 & AV8365 Network Camera Specification

4.0 Model Numbers

The camera shall be Arecont Vision model AV8365, 8 megapixel 360 degree panoramic camera

5.0 Warranty

Minimum 1 Year parts and labor

Arecont Vision reserves the right to change products or specifications without notice.